

ARCTIC™ 1% AFFF FOAM CONCENTRATE

CONCENTRATES



Description

ARCTIC™ 1% AFFF foam concentrate from SOLBERG® is a synthetic foam concentrate used to effectively extinguish Class B hydrocarbon fuel fires at 1% solution. ARCTIC 1% AFFF foam provides rapid extinguishment and excellent burn back characteristics and can be used with fresh, salt and brackish water.

Application

ARCTIC 1% AFFF foam concentrate can be applied to Class B hydrocarbon fuel fires. It is not intended for use on Class B polar solvent fuels. The foam concentrate can be used to prevent re-ignition of a liquid spill and control hazardous odors. Foam discharge devices such as non-air aspirating, as well as, air aspirating equipment, including standard sprinkler heads, can be used to obtain maximum results. The product is mixed 1 part foam concentrate to 99 parts water. It may also be used and stored as a 1% pre-mix solution. ARCTIC 1% AFFF foam concentrate is compatible with most powder (dry chemical).

Performance

Fire Performance

ARCTIC 1% AFFF foam concentrate has been tested to and meets the fire performance test criteria of Underwriters Laboratories, Inc. (UL) Standard 162 (latest edition).

Foam Proportioning

ARCTIC 1% AFFF foam concentrate can be proportioned at the proper foam solution percentage using most common proportioning devices such as:

- Eductors
- Inline balance pressure proportioners
- Ratio controllers
- Self-inducting nozzles

Storage

The temperature range for ARCTIC 1% AFFF foam concentrate is 1.7° C to 49° C (35° F to 120° F).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

Typical Physical Properties at 25°C (77°F)

Appearance:	Clear, light yellow liquid
Freezing Point:	-2.2° C (28° F) <i>(No quality loss after thawing)</i>
Maximum storage temp:	49° C (120° F)
pH:	7.0 - 8.5
Refractive index:	1.3730 - 1.3785
Specific gravity:	1.050 - 1.090
Viscosity:	4.5 - 6.5 cSt*
Sediments:	None

* Cannon-Fenske Viscometer

Compatibility

ARCTIC 1% AFFF foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing of foam concentrates, consult Solberg Technical Services.

Materials of Construction Compatibility

ARCTIC 1% AFFF foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about material compatibility, consult Solberg Technical Services.



Solberg is a global company that is a one-stop resource for firefighting foam concentrates and custom-designed foam suppression systems hardware, offering both traditional and innovative firefighting foam technology. www.solbergfoam.com



Inspection

ARCTIC 1% AFFF foam concentrate or pre-mix solutions should be inspected annually per National Fire Protection Association (NFPA) Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

Environmental Information

ARCTIC 1% AFFF foam concentrate complies with the United States

Environmental Protection Agency (USEPA) Stewardship Program—2015 Requirements.

Certifications

SOLBERG manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam’s physical parameters and the finished product’s fire performance. A Certificate of Analysis (CoA) is issued with every batch.

ARCTIC 1% AFFF foam concentrate is Underwriters Laboratories, Inc. Listed in accordance with UL 162 (Standard for Safety for Foam Equipment and Liquid Concentrates).

Ordering Information

ARCTIC 1% AFFF foam concentrate is available in pails, drums, totes and bulk quantities.

PART NO.	DESCRIPTION	APPROXIMATE SHIPPING WEIGHT	APPROXIMATE CUBE
20120	ARCTIC 1% AFFF, 20 litre (5 gallon) pail	21 kg (45 lb)	0.04 m ³ (1.25 ft ³)
20121	ARCTIC 1% AFFF, 200 litre (55 gallon) drum	224 kg (495 lb)	0.33 m ³ (11.83 ft ³)
20122	ARCTIC 1% AFFF, 1000 litre (265 gallon) tote	1118 kg (2465 lb)	1.42 m ³ (50.05 ft ³)
20123	ARCTIC 1% AFFF, bulk	Call Customer Services	

DISTRIBUTOR:



INCENDIUM AB
Rattgatan 21
SE-442 40 Kungälv
Sweden
Tel: +46 303 44 00 30
Web: www.incendiumfire.com
E-mail: info@incendiumfire.com

SOLBERGFOAM.COM

FORM NUMBER F-2011002-2_EN

COPYRIGHT © 2014. ALL RIGHTS RESERVED.
SOLBERG® AND ARCTIC™ ARE TRADEMARKS
OF THE SOLBERG COMPANY OR ITS AFFILIATES.

AMERICAS
THE SOLBERG COMPANY
1520 Brookfield Avenue
Green Bay, WI 54313
USA

EMEA
SOLBERG SCANDINAVIAN AS
Radøyvegen 721 - Olsvollstranda
N-5938 Sæbøvågen
Norway

ASIA-PACIFIC
SOLBERG ASIA PACIFIC PTY LTD
3 Charles Street
St Marys NSW 2760
Australia