

# ARCTIC™ 3x3% ATC™ FOAM CONCENTRATE CONCENTRATES



## Description

ARCTIC™ 3x3 ATC™ foam concentrate from SOLBERG® is a synthetic, alcohol-resistant foam concentrate used to effectively extinguish Class B hydrocarbon and polar solvent fuel fires at 3% solution. ARCTIC 3x3 ATC foam provides rapid extinguishment and excellent burn back characteristics and can be used with fresh, salt and brackish water.

## Application

ARCTIC 3x3 ATC foam concentrate can be applied to either Class B hydrocarbon or polar solvent<sup>††</sup> fuel fires. The product is mixed 3 parts foam concentrate to 97 parts water. It may also be used as a 3% pre-mix solution. The foam concentrate can be used to prevent re-ignition of a liquid spill and control hazardous odors. Foam discharge devices such as non-air aspirating, as well as, air aspirating equipment including standard fire sprinkler heads, can be used to obtain maximum results. ARCTIC 3x3 ATC foam concentrate is compatible with most powder (dry chemical) agents.

## Performance

### Fire Performance

ARCTIC 3x3 ATC foam concentrate has been tested to and meets the fire performance test criteria of Underwriters Laboratories, Inc. (UL) Listed – Standard 162 and FM Approval Standard 5130.

### Foam Proportioning

ARCTIC 3x3 ATC foam concentrate can be proportioned at the proper foam solution percentage using most common proportioning devices<sup>†</sup> such as:

- Eductors
- Inline balance pressure proportioners
- Ratio controllers
- Self-inducting nozzles

### Storage

The temperature range for ARCTIC 3x3 ATC foam concentrate is 1.7° C to 49° C (35° F to 120° F).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

## Typical Physical Properties at 25° C (77° F)

Appearance:	White non-Newtonian liquid
Freezing Point:	-2.2° C (28° F) <i>(No quality loss after thawing)</i>
Maximum storage temp:	49° C (120° F)
pH:	7.0 - 8.5
Refractive index:	1.3544 - 1.3594
Specific gravity:	1.000 - 1.040
Viscosity:	1840 - 2840 cP*
Sediments:	None

\*Brookfield Viscometer Spindle #4, Speed 30 rpm

## Compatibility

ARCTIC 3x3 ATC foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing of foam concentrates, consult Solberg Technical Services.



**Solberg is a global company that is a one-stop resource for firefighting foam concentrates and custom-designed foam suppression systems hardware, offering both traditional and innovative firefighting foam technology. [www.solbergfoam.com](http://www.solbergfoam.com)**

**Materials of**

**Construction Compatibility**

ARCTIC 3x3 ATC foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about material compatibility, consult Solberg Technical Services.

**Inspection**

ARCTIC 3x3 ATC foam concentrate or pre-mix solutions should be inspected annually per National Fire Protection Association (NFPA) Standards 11 and 25.

A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

**Environmental Information**

ARCTIC 3x3 ATC foam concentrate complies with the United States Environmental Protection Agency (USEPA) Stewardship Program—2015 Requirements.

**Certifications**

Solberg manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's

physical parameters and the finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.

ARCTIC 3x3 ATC foam concentrate is Underwriters Laboratories, Inc. Listed in accordance with UL 162 (Standard for Safety for Foam Equipment and Liquid Concentrates), FM Approved per Approval Standard 5130.

**Ordering Information**

ARCTIC 3x3 ATC foam concentrate is available in pails, drums, totes and bulk quantities.

<sup>†</sup> Not an FM Approved Configuration

<sup>††</sup> See FM Approval Guide

PART NO.	DESCRIPTION	APPROXIMATE SHIPPING WEIGHT	APPROXIMATE CUBE
20080	ARCTIC 3x3 ATC, 20 litre (5 gallon) pail	21 kg (45 lb)	0.04 m <sup>3</sup> (1.25 ft <sup>3</sup> )
20081	ARCTIC 3x3 ATC, 200 litre (55 gallon) drum	224 kg (495 lb)	0.33 m <sup>3</sup> (11.83 ft <sup>3</sup> )
20082	ARCTIC 3x3 ATC, 1000 litre (265 gallon) tote	1118 kg (2465 lb)	1.42 m <sup>3</sup> (50.05 ft <sup>3</sup> )
20083	ARCTIC 3x3 ATC, bulk	Call Customer Services	

DISTRIBUTOR:



INCENDIUM AB  
 Rattgatan 21  
 SE-442 40 Kungälv  
 Sweden  
 Tel: +46 303 44 00 30  
 Web: www.incendiumfire.com  
 E-mail: info@incendiumfire.com