

# RE-HEALING™ RF1, 1% FOAM CONCENTRATE

# CONCENTRATES



## Description

RE-HEALING™ RF1 foam concentrate from SOLBERG® is an innovative, environmentally sustainable fluorosurfactant and fluoropolymer-free foam concentrate used to effectively extinguish Class B hydrocarbon fuel fires. Proportioned at 1% solution, RE-HEALING RF1 foam can be used in fresh, sea or brackish water. RE-HEALING RF1 foam concentrate possesses excellent burnback resistance due to its remarkable flow and rapid resealing characteristics. RE-HEALING RF1 foam concentrate is formulated using a new high performance synthetic foam technology to replace traditional AFFF, FFFP foam concentrates and older protein and fluoroprotein foams.

## Application

RE-HEALING RF1 foam concentrate is intended for use on Class B hydrocarbon fuel fires. It is not intended for use on Class B polar solvent fuels. The foam concentrate can be used to prevent re-ignition of a liquid spill and control hazardous vapours. On Class A fuels, RE-HEALING RF1 foam concentrate

will improve extinguishment in deep-seated fires. Foam non-air aspirating discharge devices as well as air aspirating discharge devices, including standard sprinkler heads, can be used to obtain maximum results. The product is mixed 1 part foam concentrate to 99 parts water. It may also be used as a 1% pre-mix solution. RE-HEALING RF1 foam concentrate is compatible with most dry powder (chemical) agents.

## Performance

### Fire Performance

RE-HEALING RF1 foam concentrate has been tested to and meets the fire performance test criteria of European Standard EN 1568 Part 3 (latest edition).

### Foam Proportioning

RE-HEALING RF1 foam concentrate can be proportioned at the proper foam solution percentage using common foam proportioning devices such as:

- Eductors
- Inline balanced pressure proportioners
- Ratio controllers
- Self-educing nozzles



## Typical Physical Properties at 25°C (77°F)

Appearance:	Brown liquid
Freezing Point:	-14° C (7° F) <i>(No quality loss after thawing)</i>
Maximum storage temp:	49° C (120° F)
pH:	7.0 - 8.5
Refractive index:	1,4010 - 1.4090
Specific gravity:	1,135 - 1,150
Viscosity:	30 - 50 cSt
Sediments:	None

*\*Cannon-Fenske Viscometer*

## Storage

The temperature range for RE-HEALING RF1 foam concentrate is -14° C to 49° C (7° F to 120° F).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

## Compatibility

RE-HEALING RF1 foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing, consult Solberg Technical Services.



**Solberg is a global company that is a one-stop resource for firefighting foam concentrates and custom-designed foam suppression systems hardware, offering both traditional and innovative firefighting foam technology. [www.solbergfoam.com](http://www.solbergfoam.com)**

**Materials of**

**Construction Compatibility**

RE-HEALING RF1 foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about materials of construction compatibility, consult Solberg Technical Services.

**Inspection**

RE-HEALING RF1 foam concentrate or pre-mix solution should be inspected annually per National

Fire Protection Association (NFPA) Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

**Environmental Information**

RE-HEALING foam concentrates are fluorosurfactant, fluoropolymer-free products for use on Class B hydrocarbon fuels with no environmental concerns for persistence, bioaccumulation or toxic break down.

**Certifications**

SOLBERG manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters as well as the finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.

RE-HEALING RF1 foam concentrate is European Standard EN 1568 Part 3 Approved.

**Ordering Information**

RE-HEALING RF1 foam concentrate is available in pails, drums, totes and bulk quantities.

PART NO.	DESCRIPTION	APPROXIMATE SHIPPING WEIGHT	APPROXIMATE CUBE
20010	RE-HEALING RF1, 20 litre (5 gallon) pail	21 kg (45 lb)	0.04 m <sup>3</sup> (1.25 ft <sup>3</sup> )
20011	RE-HEALING RF1, 200 litre (55 gallon) drum	224 kg (495 lb)	0.33 m <sup>3</sup> (11.83 ft <sup>3</sup> )
20012	RE-HEALING RF1, 1000 litre (265 gallon) tote	1118 kg (2465 lb)	1.42 m <sup>3</sup> (50.05 ft <sup>3</sup> )
20013	RE-HEALING RF1, bulk	Call Customer Services	

DISTRIBUTOR:



INCENDIUM AB  
 Rattgatan 21  
 SE-442 40 Kungälv  
 Sweden  
 Tel: +46 303 44 00 30  
 Web: www.incendiumfire.com  
 E-mail: info@incendiumfire.com

